

## RPD-1171/ 8

1U rack mount 17" TFT monitor/keyboard drawer with optional 8-port KVM

### Industrial level input device for space-critical environments

The RPD-1171/RPD-1178 are ideal solutions to optimize your space utilization by controlling your systems in just 1U rack space.

With the RPD-1171/RPD-1178, you can control up to eight platforms and easily expand the connections up to 512 systems with the combination of KVM switch boxes. The RPD-1171 and RPD-1178's 17-inch TFT LCD display and keyboard/touchpad provide a reliable and user friendly input environment. All of these functions are integrated into a 19-inch wide, 1U high space with rugged construction design to achieve ultra space saving and high availability for industrial/network applications.



### Features include:

- High brightness 17-inch TFT LCD display support SXGA ( 1280 x 1024 )resolution
- Dual inputs for analog and DVI signals (option for RPD-1171 only)
- Durable keyboard/touchpad or trackball
- OSD function (On Screen Display) for LCD display and KVM Switch
- Built-in power supply
- Built in KVM switch function for easy controlling and monitoring of up to 8 residing servers/platform ,or up to 512 systems by cascading (RPD-1178 only)

### RPD-1171/ 8 - Technical Specifications

#### Mounting

- Rack mount, 19-inch (482.6mm)

#### Display Type

- LCD, TFT panel display with built-in power saving and back light protection functions

#### Display Size

- 17-inch diagonal

#### Viewing Area (W x H)

- 337.92 x 270.34mm (13.3 x 10.64inch)

#### Dimensions (W x H x D)

- 17.34 x 1.73 x 21.65-inch (440 x 44 x 550mm)

#### Contrast Ratio

- 400:1 (typical)

#### Viewing Angle

- Horizontal: 70/70 degrees (typical)
- Vertical: 70/70 degrees (typical)

#### Display Colors

- 16.2 million (RGB 6-bit)

#### Maximum Resolution

- SXGA (1280 x 1024)

#### Brightness

- 260 nit

#### Response Time

- Tr:12 ms
- Tf:4 ms

#### Interface

- Analog RGB input
- DVI input (option for RPD-1171 only)

#### LCD Controller

- Genesis gm5120 LCD controller

#### Scanning Frequencies

- Vsync: 57 ~ 75Hz
- Hsync: 80 kHz

#### Backlight

- Backlight automatically shuts off when display is closed

#### Pixel Pitch (H x V)

- 0.264 x 0.264mm

#### LCD panel protection

- Tempered galss to protect LCD panel

#### Cable Connector

##### RPD-1171

- 15-pin DSUB
- DVI-D connector (optional)

##### RPD-1178

- DB25 keyboard/video/mouse input

#### KVM Switch (RPD-1178 only)

- KVM switch control: Front panel switch, hotkey & OSD control
- KVM support: Up to eight systems; cascade to three levels, up to 512 systems

#### Monitor Control Type

- Digital microprocessor OSD control

#### VESA Plug-n-Play Level

- DDC1 and DDC2B

#### Screen Adjustment Controls

- Menu, auto adjustment, brightness, contrast, phase, H/V position, zoom, color, OSD position, etc.

#### Power Management

- VESA DPMS, EPA/Energy Star compliant

#### Keyboard

- PS/2, 84-key computer keyboard (RPD-117\*B only)
- PS/2, 88-key notebook keyboard with numeric keypad (option for RPD-117\*C only)

#### Integrated Pointing Device

- PS/2, high-quality 16mm trackball (RPD-117\*B only)
- PS/2, high-quality touchpad (RPD-117\*C only)

#### Construction

- SECC

#### Housing

- Meets EIA RS-310C 1U 19-inch rack mount standard

#### Color

- Black

#### Weight

- 30.8lb (14kg)

#### LCD Life

- 40,000hrs for backlights

#### Power Supply

- Input: 115 to 230VAC, 1.8A, 50/60Hz, 2/1A
- Output: 12VDC @3A, 2.5W per channel
- Type: AC PSU auto-switching

#### Power Consumption

- 26.25W (typical), 36W (max)

#### Operating Environment

##### Temperature

- 0 ° to 45 °C (32 ° to 113 °F)

##### Humidity

- 20 to 90% @ 40 °C (104 °F), non-condensing

##### Vibration

- 10 to 58Hz, ± 0.075mm; 58 to 500Hz, 1g

#### Non-Operating Environment

##### Temperature

- -20 ° to 60 °C (-4 ° to 158 °F)

##### Humidity

- 5 to 95% @ 40 °C (104 °F), non-condensing

##### Vibration

- 10 to 58Hz, ± 0.15mm; 58 to 500Hz, 2g

#### Agency Approvals

- CE/FCC Part 15, Class AII
- EN 60950 Safty

#### Support

- Superior pre- and post sales technical support
- Two year limited warranty

#### Ship Kit

- 1U monitor/keyboard drawer
- AC power cord
- One 1.8-meter KVM cable (RPD-1178 only)
- Support CD containing user's manual



### Ordering Guide

#### RPD-1171B

1U 17-inch TFT monitor/keyboard drawer with Cherry keyboard and trackball

#### RPD-1171C

1U 17-inch TFT monitor/keyboard drawer with notebook keyboard and touchpad

#### RPD-1178B

1U 17-inch TFT monitor/keyboard drawer with 8-port KVM, Cherry keyboard and trackball

#### RPD-1178C

1U 17-inch TFT monitor/keyboard drawer with 8-port KVM, notebook keyboard and touchpad