

C-Drive

C-Drive



Features

- The compact value drive housing kit can hold slim-type CD-ROM /FDD within standard 5.25" drive space
- More flexible in limited drive space
- Rugged design for industrial application
- Quality device for high reliability
- Integrated with slim type 24 x CD-ROM and floppy
- Standard desktop IDE & FDD connector
- Standard 5.25" Drive mounting hole

Ordering Guide

Model Name	Color
C-Drive-DVD-BLK BGE	Slim 8 xDV D +1FDD in black/beige color
C-Drive-BLK	Slim 24 x CD-ROM +1FDD in black color
C-Drive-BGE	Slim 24 x CD-ROM +1FDD in beige color

Specification

Construction

Heavy duty steel for industrial application

Drive Bays

External: 1 x slim 24X CD-ROM + 1 x FDD

Mounting Holes

Standard 5.25" drive holes reserved

Temperature and Humidity

Operating : 5 ~ 55 °C , 20 ~ 80% RH

Storage : -30 ~ 70 °C , 5 ~ 90% RH

Power Consumption

CD-ROM +5V@ 1.5A(MAX)

FDD +5V @ 0.8A (max) / 0.26A (typ) / 0.002A (stb)

MTBF

CD-ROM 60,000 POH

FDD 15,000 POH

Dimension

148.4 (W) x 185 (D) x 42 (H) mm

Weight

Gross : 1.20Kg

All specifications are subject to change. For the up-to-date information, please visit our website.